BONA TECHNOLOGY CO., LTD.

ADD: T4-2410, Fucheng International, No. 722 Yizhou Ave.,

Hi-Tech Zone, Chengdu, China

TEI: +86 (28) 6577 7287

FAX: +86(28) 6577 7291

E-mail: info@bonatechnology.com
Http://www.bonatechnology.com



Introduction







Located in Chengdu, a city has 4,500 years urban civilizations and is famously known as Land of Abundance with unique natural and endowments and long-lasting prosperity, Bona Technology Co., Ltd. has become one of the most energetic advocates of industrial application on Hi-tech equipment, advanced materials, and green energy. We take pride in dedicating ourselves to this as our primary mission to make the world running safer, healthier and more effective. Bona Technology has dedicated over 10 years worldwide in design, supply and installation in industrial lighting projects. Knowing more than products, we provide Professional Lighting Solutions. We maintain our business reputation like we value our lives.

Our lighting factory, branded as YASHIPS LIGHTING, is a manufacturing enterprise specializing in indoor & outdoor public lighting products since 1988 on LED/HID bulbs, lighting fixtures of Road Light, Flood Light, High-bay, Tunnel, Wall-pack, Ceiling, Post-top, Bollard and electrical ballast, igniter and capacitor.

We have complete production equipment with die-casting machines, CNC machining center, Laser cutting and bending machines, automatic powder coating lines, SMT process lines, final assembling and testing workshops, as well as automatic production lines for bulbs in house. 6% of the annual turn-over goes in R&D, supporting a professional and complete R&D team with 60 engineers, covering Mechanical, Optical design, Thermal, Electronics and Molding.

To ensure the reliable quality, our factory has built an international standard test center recognized as Strategic Cooperation Lab by INTERTEK-USA and TUV-Germany. The products are tested in accredited ISO/IEC 17025 Lab and certified with CE, CB, ENEC, ETL, DLC and RoHS complied. All products must pass through a series of strict inspection. The ex-factory qualification rate has reached 99.7%.

The factory has passed ISO9001, ISO 14001, OHSAS 18001 international quality, environment, health & safety management. And honorably, we are a member entity for developing China National Standards on LED Lighting.

Honor | Certificate

















































Equipments **Equipments**

We have complete production facilities die-casting machines, CNC machining center, Laser cutting, bending machines, automatic powder coating, SMT process and final assembling and test, as well as automatic production lines for bulbs in house. A complete strong R&D team composed with Structural Mechanical, Optical design, Thermal, Electronics & Molding.

Products have test in accredited ISO/IEC17025 Lab and certified with CE,CB,ENEC,ETL,DLC and RoHs complied.
























LEO Bolb			Ground Buried Lights	52	YZWL632
			Post-Top Light	53-60	YXL861-P YZTL851 YZTL850 YXL172-P YZTL858
LED Bulb	01-08	YSC37 YSG45/50 YSA60/65/70/80/95			YZTL852 YZTL853 YZTL856 YZTL855 YZTL857
		YST60/80/100/120/140 YSR39/50/63/80/90			YZTL863 YZTL864 YZTL890 YZTL862
		YSG80/95/120/125 YSGU10 YSMR16 YSPAR20/30/38			YZTL859 YZTL860
			Bollard Light	61-62	YZTL813 YZTL815 YZTL811 YZTL812
Road & Tunnel Light					
THE STATE OF THE S			Industrial Light		•
	10	Light Distribution Curve			
Road Light	11-21	YZDL751 YZDL752 YZDL759 YZDL761		64	Light Distribution Curve
		YZDL749 YZDL750 YXL861-D	High-Bay Light	65-70	YGCL542 YXL324-G
		YZDL734 YZDL741 YZDL736 YZDL760			YGCL545 YXL536-G YGCL546 YXL538-G
		YZDL754 YZDL732 YZDL784 YZDL783			YGCL540 YGCL541 YGCL546
		YZDL788 YZTL891	Canopy Light	71-72	YGWL132 YGWL133 YXL313-W
Guardrail Light	22	YYGL490			YXL536-W YXL538-W YXL137-W
Tunnel Light	23-24	YZDL721 YZDL725 YZDL723 YXL321-S YXL734-S	Gas Station Light	73	YGWL117
Solar Road Light	25-26	YZDS792 YZDS736 YZDS759 YZDS760 YZDS761	Anti-corrosion Light	74	YXL172-F
Smart Street Light	Smart Street Light 27-28 Smart Street Light		Anti-explosion Light	75-77	YFBL196-D YFBL196-T
					YFBL197-T YFBL197-B YFBL198-C YFBL200-Y
Landscape Light	· ·		Fire Emergency Light&Sign lamp	78	YFBL201-XZ YFBL201-XB
			Anti-Explosion Headlight&Flashlig	ht 79-80	YFBL202 YFBL203
	30	Light Distribution Curve			
Flood Light	31-40	YXL324-T YGTL330	Rail Traffic & Indoor Light	11	•
		YXL322-T YXL321-T YXL323-T			
		YGTL329 YGTL304 YGTL312		82	Light Distribution Curve
		YGTL318 YGTL305 YXL137-T YXL164-T YXL320-T	Compartment Tunnel Light	83	YZDL722
		YGTL325 YGTL303 YGTL302 YXL313-T	Classroom Light&Blackboard Light	84	YGPL271 YGPL270
Point Light	41-42	YGDL031 YGDL012 YGDL013 YGDL026 YGDL027	Panel Light	85-86	YGPL200 YGPL202 YGPL203 YGPL251 YGPL201
Linear Light	43-44	YYGL401 YYGL410	Bracket Light	87-88	YGPL205 YGPL206 YGPL204
Wall Washer	45-47	YYGL411 YYGL423 YYGL436 YYGL437	Down Light	88-90	YGPL252 YGPL253 YGPL254 YMXL255 YGPL256
Corrugated Light&Hug tree Light	48	YGDL061 YLHL070	Emergency Safety Sign Lamp	90	YGPL260
Wall-Pack Light	49-52	YGWL160 YGWL166 YGWL167 YGWL169 YGWL168			

YGWL163 YXL164-B YGWL182 YXL313-B





LED energy saving bulb

Candle bulb,G45-G50,A bulb,T bulb,G bulb,Spot light,R lamp

Dimmable bulb

- 1. Silicon dimmable
- 2. Brightness dimmable
- 3. Color temperature dimmable
- 4. Memory graded dimming and color tempering

Induction bulb

Light sense / radar/ infrared

Light sense:

- 1. Light on when <20LUX and off when >40LUX.
- 2. Smart light sense: Zero-distance work of multiple light sources without mutual interference. Radar: Sensing range diameter 10m

Smart bulb

Communication method: BT WIFI ZIGBEE
Function: Color temperature, brightness,RGB colorful
Control method: Remote control, Smart mobile terminal

New energy efficiency bulb

New energy efficiency regulation bulbs reach 120ml/W, 140LM /W, 160lm/W

Healthy lighting

Ra>97, lowest blue light radiation<2%, flashing PST<1. Flickering index SVM<0.4





Smart Light Sense








Multiple lamps work at the same time without interfere.

Model: YSG45 / YSA60 / YSA70 / YSG120 / YST100



Radar Sensing Bulb





Sufficient brightness, light off when human enter induction area.



Insufficient brightness, light on when human enter induction area.



Insufficient brightness, light on continuously with human activities in induction area.



Insufficient brightness, automatically light off after human leave induction area 15-25 seconds.

Sensing range:diameter 10m

Model: YSG45 / YSA60 / YSA70 / YSG120 / YST100



Smart Bulb



Function







Brightness

RGB colorful

Color temperature

Communication method







BT

WIFI

ZIGBEE

Cloud platform





Google Assistant

Amazon Alexa





Flexibly Switch Model: YSC37 / YSG45 / YSA60 / YSGU10

LED BULB





YSC37

[Power] 3W~9W [Beam Angle] 270°

3W/5W/6W: E14:36.6×99mm [Size]

E27:36.6×101mm E14 C37 candle: 36.6 × 125mm E27 C37 candle:36.6×126.3mm

E14:37×107mm

E14 C37 candle: 37 × 131 mm

E27:37×106mm E27 C37 candle:37 × 130mm

E14:37×114mm E14 C37 candle:37×138mm

E27:37×109.5mm

E27 C37 candle:37 × 133.5mm





YSG45/50

[Power] 3W~9W [Beam Angle] 270°

[Size]

3W/5W/6W: E27:45×80.2mm E14:45×80mm B22:45×78.2mm G50 E27:45×79.5mm 7W:

E27:47×88.5mm E14:47×88.5mm B22:45×86.5mm

9W:

E27:46×80mm E14:46×80mm B22:46×78mm

YSA60

12W:

[Power] 5W~15W [Power] [Beam Angle] 270° [Beam Angle] 270° 5W/7W: E27:60×108mm [Size] [Size] E27:66×132mm B22:66×130mm B22:60×106mm E27:60×112mm

YSA80 B22:60×110mm

E27:60×118mm [Power] B22:60×116mm [Beam Angle] 270° 13W/15W: E27:60×123mm [Size] E27:81×145mm B22:60×121mm B22:81×142mm

YSA65

YSA70

15W/18W [Power] 15W/18W [Beam Angle] 270° [Size] E27:69.5×134mm

YSA95

18W/20W [Power] 24W [Beam Angle] 270°

> [Size] E27:95.3×162mm B22:95.3×160mm

B22:69.5×132mm

/01 LED Bulb / 02

LED BULB







V	S	T	6	n

[Power] 9W [Beam Angle] 270°

E27:60×118mm B22:60×116mm

YST120

40W [Power] [Beam Angle] 270°

E27:117.5×201mm B22:117.5×199mm [Size]

YST80

[Power] 18W [Beam Angle] 270°

[Size] E27:80×142.5mm B22:80×140.5mm

YST140

50W [Power] [Beam Angle] 270°

E27:137×230mm B22:137×228mm [Size]

YST100

[Power] 28W [Beam Angle] 270°

E27:100×180mm [Size] B22:100×178mm

YSG80

[Power] 10W [Beam Angle] 270°

[Size] 80×121mm

YSG95

[Power] 12W [Beam Angle] 270°

E27:95×141.5mm B22:137×139.5mm

YSG120

[Power] 18W [Beam Angle] 270°

E27:120×164mm [Size] B22:120×162mm

YSG125

[Power] 24W [Beam Angle] 270°

E27:125×176.5mm B22:120×174.5mm [Size]

/03 LED Bulb / 04

LED BULB









YSR39

[Power] 3W [Beam Angle] 120°

[Size]

E14:39.5×69mm

YSR80

15W [Power] [Beam Angle] 120°

E27:80×115mm B22:80×113mm [Size]

YSR50

[Power] 5W [Beam Angle] 120°

[Size] E14:50×86mm

YSR90

20W [Power] [Beam Angle] 120°

E27:90×116.5mm B22:80×114.5mm [Size]

YSR63

[Power] 10W~12W [Beam Angle] 120°

[Size]

E27:63.5×100mm B22:63.5×98mm

YSGU10

[Power] 5W~8W [Beam Angle] 38°/60° 49.2×53.7mm [Size]

YSPAR20

[Power] 9W [Beam Angle] 38°

[Size] 63.5×85mm

YSMR16

[Power] 5W/6W [Beam Angle] 38°/60° [Size] 49.2×53.7mm

YSPAR30

[Power] 13W [Beam Angle] 38° [Size] 95×91.5mm

YSPAR38

[Power] 18W [Beam Angle] 38°

[Size] 121×125mm

/ 05 LED Bulb / 06





Light distribution curve (Applicable items)

YZDL751/752/759/749/750






YZDL761/320-D/164-D/741/736/734/754/792/732






XL861-D









YZDL721/YZDL723/YZDL725/YXL321-S/YXL734-S













40W~150W [Power] 110-150 lm/W [Efficiency] [Beam Angle] TYPE II/III [Size A] 568X222X107mm [Size B] 630X280X107mm [Size C] 748X320X116mm





YZDL752



40W~320W [Power] [Efficiency] 110-150 lm/W [Beam Angle] TYPE II/III [Size A] 593X221X98mm [Size B] 651X257X112mm [Size C] 753X284X122mm [Size D] 824X320X115mm [Size E] 890X369X118mm



[Power]

[Efficiency] 110-150 lm/W [Beam Angle] TYPE II/III [Size A] 545X232X100mm [Size B] 622X262X100mm 731X288X100mm [Size C]

40W~200W

YZDL761

40W~240W [Power] [Efficiency] 110-150 lm/W [Beam Angle] TYPE II/III 446X194X87mm [Size M] [Size A] 476X207X92mm 541X258X92mm [Size B] 663X284X92mm [Size C] [Size D] 723X312X92mm






[Power] 40W~240W [Efficiency] 110-150 lm/W [Beam Angle] TYPE II/III

YZDL749

[Size A] 552X220X114mm [Size B] 679X290X127mm [Size C] 794X330X128mm [Size D]






YZDL750

[Power] 40W~150W [Efficiency] 110-150 lm/W [Beam Angle] TYPE II/III

584X262X111mm [Size A] 627X262X114mm [Size B] [Size C] 737X313X118mm









YXL861-D


[Power] 60W~120W [Efficiency] 110-150 lm/W [Beam Angle] TYPE II/III 660X510X115mm

> 562X510X215mm Ф510X180mm









/11

YZDL734

[Efficiency]

[Beam Angle] TYPE II/III

[Power]

[Size]

/13





[Power] 40W~300W [Efficiency] 110-170 lm/W [Beam Angle] TYPE II/III


[Size A] 1-Modular:489X285X108mm

1-Modular:499X285X108mm 2-Modular:553X285X108mm 2-Modular:573X285X108mm

3-Modular:663X285X108mm

[Size B] 2-Modular:600X343X120mm

3-Modular:680X343X120mm 4-Modular:760X343X120mm 5-Modular:840X343X120mm





100W~360W

110-170 lm/W

2-Modular:605X345X125mm

3-Modular:685X345X125mm

4-Modular:765X345X125mm

5-Modular: 845X345X125mm

6-Modular:925X345X125mm



YZDL741

[Power] 120W~150W [Efficiency] 110-170 lm/W [Beam Angle] TYPE II/III [Size] 730X343X135mm



YZDL760

 [Power]
 30W~60W

 [Efficiency]
 110-130 lm/W

 [Beam Angle]
 TYPE II

 [Size]
 396X163X78mm





YZDL754

[Power] 60W~240W [Efficiency] 110-170 lm/W [Beam Angle] TYPE II/III

[Size] 1-Modular:448X330X91mm

THE RESERVE TO THE PARTY OF THE


2-Modular:448X330X91mm 3-Modular:528X330X91mm 4-Modular:608X330X91mm

5-Modular:688X330X91mm



YZDL732

[Size B]



[Power] 40W~240W [Efficiency] 110-150 lm/W [Beam Angle] TYPE II/III [Size M] 440X200X116mm [Size A] 626X306X118.5mm

761X353X114mm

YZDL784

[Power] 40W~240W [Efficiency] 110-170 lm/W [Beam Angle] TYPE II/III

[Size A] 720X335X160mm [Size B] 960X380X240mm

YZDL783

[Power] 40W~300W [Efficiency] 110-170 lm/W [Beam Angle] TYPE III [Size] 750X340X210mm

890X390X240mm

/15





LED GUARDRAIL LIGHT







YZTL891

[Power] 30W~100W [Efficiency] 100-130 lm/W [Beam Angle] TYPE II/III

[Size] 700X360X840mm (Size can be customized)

YYGL490

[Power] 12W~24W [Efficiency] 100-120 lm/W [Beam Angle] 16°X45°

[Size] 2120X150X235mm



LED TUNNEL LIGHT






YZDL721

[Power] 40W~240W [Efficiency] 110-150 lm/W

[Beam Angle] 90°/ 90°X110°/ 120°X140° [Size] 40W:359X104X115mm

60W:463X104X115mm 90W:619X104X115mm 120W:480X160X115mm 150W:590X160X115mm 180W:645X160X115mm 240W:810X160X115mm



YZDL725

[Power] 40W~180W [Efficiency] 110-130 lm/W

[Beam Angle] 90°/ 90°X110°/ 120°X140°

[Size]

1220X300X140mm 1220X200X140mm 1220X100X140mm



YZDL723

[Power] 30W [Efficiency] 110-130 lm/W [Beam Angle] 90°/ 90°X110° [Size] 1000X65X90mm


YXL321-S

[Power] 35W~300W [Efficiency] 110-170 lm/W [Beam Angle] 90°/ 90°X110°

[Size] 1-Modular:319X82X118mm

2-Modular: 325X149X166.5mm 3-Modular: 325X228X166.5mm 4-Modular: 325X307X166.5mm

5-Modular: 325X386X166.5mm



YXL734-S

[Power] 60W~300W [Efficiency] 110-170 lm/W [Beam Angle] 90°/ 90°X110° [Size] 360X335X190mm 360X415X190mm 360X495X190mm

/ 21 Road And Tunnel Light / 22

LED SOLAR ROAD LIGHT





YZDS759

[Power] 40W~200W [Efficiency] 110-150 lm/W [Beam Angle] TYPE II/III

YZDS760

 [Power]
 20W~60W

 [Efficiency]
 130-160 lm/W

 [Beam Angle]
 TYPE II/III


YZDS761

[Power] 100W~120W [Efficiency] 130-160 lm/W [Beam Angle] TYPE II/III

LED SMART STREET LIGHT







Light distribution curve

(Applicable items)



Universal light distribution





















































YGWL163/166/YXL164C/D-B













YGWL169/YZTL850












YZTL811/812













YXL324-T

[Size]

200W~720W [Power]

Single lens: 70-80 lm/W Module: 110-150 lm/W [Efficiency]

[Beam Angle] Single lens: 4°/ 10°/ 24°/ 30°/ 60° Module: 15°/ 30°/ 60°/ 90°

1-Modular: 645X135X300mm 2-Modular: 665X135X555mm 3-Modular: 690X135X770mm









YGTL330

240W~480W [Power] [Efficiency] 120-150 lm/W [Beam Angle] 30°/60°/90° [Size A] 440X535X65mm [Size B] 655X535X80mm





Landscape Lighting / 30 /29



YXL322-T

360W~1200W [Power] [Efficiency] 110-170 lm/W [Beam Angle] 15°/30°/60°/90°

[Size]

6-Modular: 352X140X716mm 8-Modular: 432X140X716mm 10-Modular: 527X140X716mm 12-Modular:592X140X716mm 14-Modular:672X140X716mm 18-Modular:592X140X1070mm 21-Modular:672X140X1070mm





YXL321-T

[Power] 180W~1200W [Efficiency] 110-170 lm/W [Beam Angle] 15°/30°/60°/90°

[Size]

3-Modular:325X111.6X270mm 4-Modular:325X111.6X349mm 5-Modular:325X118X428mm 6-Modular:325X118X508mm 8-Modular:325X118X508mm 8-Modular:399X110.4X706mm 10-Modular:478X110.4X706mm 12-Modular:557X110.4X706mm 14-Modular:636X110.4X706mm 18-Modular:557X110.4X1023mm 21-Modular:636X110.4X1023mm

YXL323-T

200W~240W [Power] [Efficiency] 110-130 lm/W [Beam Angle] 15°/30°/60°/90° 335X85X486mm [Size]



Landscape Lighting / 32 /31



YGTL329

[Power] 10W~200W 100 lm/W [Efficiency] [Beam Angle] 60°/90°/110° [Size A] 110X29X175mm [Size B] 170X31.5X190mm 220X40X212mm [Size C] [Size D] 285X41.5X315mm 280X54.5X385mm [Size E] [Size F] 340X55X430mm









YGTL304

50W~120W [Power] [Efficiency] 110-150 lm/W [Beam Angle] 6°/10°/15°/30°/60°

[Size A] Bracket: 246X197X280mm Slip-fitter: 246X200X316mm

Bracket:320X246X362mm Slip-fitter:320X246X398mm [Size B]

Bracket







Slip-fitter





YGTL312

[Power] 18W~150W [Efficiency] 80-100 lm/W [Beam Angle] 6°/10°/15°/30°/60° 172X110X213mm [Size B]

1-Modular: 218X131X274mm [Size C]

2-Modular: 425X131X274mm 3-Modular: 626X131X274mm



/ 33 Landscape Lighting / 34



YGTL318

[Power] 30W~200W [Efficiency] 90-100 lm/W

[Beam Angle] 110°

[Size] 30W:210X30X165mm 50W:240X33X205mm

70W:240X45X205mm 100W:300X45X258mm 150W:248.5X51.7X382.4mm 200W:308.1X51.7X478.3mm



YGTL305

[Power] 20W~80W [Efficiency] 80 lm/W [Beam Angle] 30°/60°/90° [Size A] 168X80X132mm [Size B] 290X115X195mm



YXL137-T

[Power] 70W~280W [Efficiency] 110-130 lm/W [Beam Angle] 15°/ 30°/ 60°/ 90° [Size A] 389X113.5X412mm [Size B] 491X127.5X514mm



YXL164-T

[Power] 50W~180W [Efficiency] 110-170 lm/W [Beam Angle] 15°/30°/60°/90°

[Size B] Bracket: 261.9X70.5X327.5mm Slip-fitter: 262X71X366mm

[Size C] 271X72X368mm [Size D] 273X81X490mm



Bracket



G1/2 Slip-fitter







YXL320-T

[Power] 60W~200W [Efficiency] 110-150 lm/W [Beam Angle] 60°/90°

[Size A] 292X73X400mm [Size B] 292X73X543mm

/ 35 Landscape Lighting / 36



YGTL325

[Power] 1W~6W [Efficiency] 80-100 lm/W

[Beam Angle] $4^{\circ}/6^{\circ}/10^{\circ}/15^{\circ}/30^{\circ}/45^{\circ}/60^{\circ}$

[Size A] Φ37X75X80mm [Size B] Φ67X115X115mm





YGTL302

[Power] 9W~50W [Efficiency] 80-100 lm/W [Beam Angle] 6°/10°/15°/30°/60° [Size A] 150X80X160mm [Size B] 222X110X245mm



YGTL303

[Power] 6W~12W [Efficiency] 80-100 lm/W [Beam Angle] 6°/10°/15°/30°/60° [Size A] 115X80X130mm

Hoop type







YXL313-T

[Power] 50W~70W [Efficiency] 80-100 lm/W [Beam Angle] 10°/15°/30°/60° [Size] 246X170XΦ222mm



Landscape Lighting / 38

LED POINT LIGHT



YGDL031

[Power] 9W~18W

[Voltage] DC24V/AC220V

[Beam Angle] 150°

Ф120X204X155mm Ф120X124X174.8mm [Size]















YGDL012

[Power] 0.75W~1.5W [Voltage] DC12V

[Size A] Ф32X13.5mm [Size B] Φ42X15.5mm

[Beam Angle] 120°



YGDL013

[Power] 0.5W~0.75W DC12V [Voltage] [Beam Angle] 120°

22X22X14.2mm [Size A] 29.6X29.6X14.5mm [Size B]



YGDL026 [Power]

[Beam Angle] 120° [Size A] 77X28mm

[Voltage]

[Size B] 120X43mm

1W~5W

DC24V



Transparent cover



Milky white cover

YGDL027

[Power] 3W~4.5W [Voltage] DC24V [Beam Angle] 120°

[Size] 76X44.7mm

/ 39 Landscape Lighting / 40

LED LINEAR LIGHT



YYGL401

10W~12W [Power] DC24V [Voltage] [Beam Angle] 120°

[Size A] A-R:1000X34.8X51.2mm

A-F:1000X34.6X47.7mm

[Size B] B-R:1000X44.2X60.5mm

B-F:1000X44.2X60.5mm

YYGL410

10W~24W [Power] DC24V [Voltage]

[Beam Angle] 30°/45°/60°/120° [Size A] 1000X20X50mm 1000X20X45mm [Size B] [Size C] 1000X28X38mm 1000X57X35mm [Size D]





/41

LED WALL WASHER

YYGL411

[Power] 10W~36W DC24V/AC220V [Voltage]

[Beam Angle] 30°/45°/60°/10°X60°/20°X40°/120°

M-N:1000X28X74mm M-Z:1000X28X92mm [Size M]

L-N:1000X35X68mm [Size L] L-Z:1000X35X88mm

[Size A]





YYGL423

[Size C]

18W~120W [Power] [Voltage] DC24V/AC220V

[Beam Angle] 30°/45°/60°/10°X60°/20°X40°

A-N:1000X41X81mm A-Z:1000X41X110mm [Size A]

B-N:1000X60X141mm

[Size B] B-Z:1000X60X167mm

C-N:1000X81X160mm C-Z:1000X81X186mm

YYGL423C-N YYGL423C-Z

/43 Landscape Lighting / 44

LED WALL WASHER(Two-side output)

LED CORRUGATED LIGHT



YYGL436 Wall washer + Contour

Regular:18W~24W Optional:10W

DC24V [Voltage]

[Beam Angle] 30°/45°/60°/10°X60°/20°X40°

[Size]

1000X65X114mm

YGDL061

6W~12W [Power] DC24V/AC220V [Voltage] [Beam Angle] 10°/15°/30°/60° 225X67X100mm [Size]



LED HUG TREE LIGHT

YLHL070

[Power] [Voltage] 36W~96W DC24V/AC220V

80 lm/W [Efficiency] [Beam Angle] 15°/45°/60°

[Size]

6-Modular: Φ510X343mm



YYGL437 Wall washer + Light guide

[Power]

Regular:18W~24W Optional:10W

DC24V [Voltage]

[Beam Angle] 30°/45°/60°/10°X60°/20°X40°

[Size]

1000X58.5X106mm

/45

LED WALL-PACK LIGHT



YGWL160

[Power] 40W~100W [Efficiency] 110-130 lm/W [Beam Angle] 90°X105° 364X180X230mm [Size]



YGWL166

40W~120W [Power] [Efficiency] 110-150 lm/W

[Beam Angle] TYPE II/ TYPE III/ TYPE IV 364X220X230mm [Size]



YGWL167

8W~12W [Power] [Beam Angle] TYPE II/ TYPE III 230X90X90mm [Size]





YGWL167B

[Power]

YGWL169

25W~35W 90-110 lm/W [Efficiency] [Beam Angle] 120°

[Size] 350X265X475mm



YGWL168

[Power] 9W~12W [Efficiency] 90-100 lm/W

[Beam Angle] 10°

[Size] 358X147X134.5mm



[Power] 18W~60W 110-150 lm/W [Efficiency] [Beam Angle] TYPE II/ TYPE III/ TYPE IV

[Size A] 150X75X150mm [Size B] 272X77X206mm



Landscape Lighting / 48 /47

LED WALL-PACK LIGHT





YGWL182

9W~24W [Power] [Efficiency] 100-120 lm/W [Beam Angle] 18°/24°/36°

Single-side output: Φ127X200X189mm Two-side output: Φ127X300X190mm [Size]



YXL313-B

50W~120W [Power] [Efficiency] 110-130 lm/W [Beam Angle] 10°/15°/30°/60°

[Size]

Single-side output: Φ224X286X266mm Two-side output: Φ224X358X266mm

YXL 164-B

50W~180W [Power] 110-170 lm/W [Efficiency]

[Beam Angle] TYPE II/ TYPE III/ TYPE IV

262X115X299mm [Size B] 271X120X355mm [Size C] [Size D] 273X120X468mm

LED GROUND BURIED LIGHT

YZWL632

[Power] 1W~36W [Efficiency] 70 lm/W [Beam Angle] 30°/45°/60° [Size S] Ф70X100mm [Size M] Ф100X75mm [Size A] Ф150X118mm [Size B] Ф180X118mm Ф210X118mm [Size C] Ф250X118mm [Size D]





/49 Landscape Lighting / 50

LED POST TOP LIGHT

YZTL851

[Power]

45W~120W

Ф545X570mm

[Beam Angle] 120°/ TYPE IV/ TYPE V

[Efficiency] 90-110 lm/W





60W~120W [Power] [Efficiency] 110-130 lm/W [Beam Angle] TYPE IV/ TYPE V Φ510X540mm [Size]



YZTL850

[Power] 35W~50W [Efficiency] 90-110 lm/W [Beam Angle] 120°

Ф560X500mm [Size]



YXL172-P

40W~60W [Power] [Efficiency] 110-130 lm/W [Beam Angle] 180°

[Size] Ф428X294mm



YZTL858

45W~60W [Power] [Efficiency] 80-100 lm/W

[Beam Angle] 120°

Φ580X425mm [Size]





LED POST TOP LIGHT







[Power] 45W~120W [Efficiency] 90-110 lm/W [Beam Angle] 120°/ TYPE IV/ TYPE V

[Size] Ф560X665mm



[Power] 45W~120W [Efficiency] 90-110 lm/W

YZTL855

[Beam Angle] 120°/ TYPE IV/ TYPE V [Size] Ф560X665mm



45W~80W [Power] [Efficiency] 90-110 lm/W [Beam Angle] 120°/ TYPE IV/ TYPE V

Φ425X545mm [Size]





[Size]

45W~120W [Power] [Efficiency] 90-110 lm/W [Beam Angle] 120°/ TYPE IV/ TYPE V

Ф522X745mm



[Power] 45W~100W [Efficiency] 60-80 lm/W [Beam Angle] 140° [Size] Ф458X890mm



LED POST TOP LIGHT







[Power] 30W~100W [Efficiency] 90-110 lm/W [Beam Angle] 140° [Size] Ф590X515mm

YZTL864

[Power] 30W~60W [Efficiency] 100-120 lm/W [Beam Angle] 120° [Size] Ф458X890mm





[Power]

30W~60W [Efficiency] 90-110 lm/W [Beam Angle] 120°

Φ654X620mm [Size]

YZTL862

YZTL890

30W~60W [Power] [Efficiency] 90-110 lm/W

[Beam Angle] 120°

[Size] Ф500X700mm

LED POST TOP LIGHT





YZTL859

25W~120W [Power] [Efficiency] 90-110 lm/W [Beam Angle] 120°/ TYPE IV/ TYPE V 265X265X456mm [Size A]

[Size C] 385X385X695mm



[Power] 70W~80W 90-110 lm/W [Efficiency] [Beam Angle] TYPE IV/ TYPE V [Size A] Φ470X605mm Φ445X120X730mm [Size B]



LED BOLLARD LIGHT





YZTL813

25W~35W [Power] [Beam Angle] 120°

[Size] Ф208X800mm



YZTL815

[Power] 9W~18W [Beam Angle] 120°

[Size A/B] Ф153X812.8mm [Size C/D] Φ153X800mm Note: A/C is bulb type, B/D is LED type



YZTL811A

[Power] 25W [Beam Angle] 150° [Size] Ф165X800mm

YZTL812A

[Power] 25W~35W [Beam Angle] 150°

[Size] Ф213X800mm



YZTL811B

[Power] 25W~35W [Beam Angle] 150°

Ф165X800mm [Size]

YZTL812B

25W~50W [Power] [Beam Angle] 150°

[Size] Ф213X800mm



YZTL811C

[Power] 25W [Beam Angle] 150°

[Size] Ф165X800mm

YZTL812C

25W~35W [Power] [Beam Angle] 150°

Ф213X800mm [Size]



YZTL811D

[Power] 25W~35W [Beam Angle] 150°

[Size] Ф165X800mm

YZTL812D

25W~50W [Power]

[Beam Angle] 150°

[Size] Ф213X800mm

/59 Landscape Lighting / 60



Light distribution curve (Applicable items)




YXL324-G/YXL137-W/117







YGCL545







YGCL540/541




YGCL546

YGCL542











YXL536
















YGWL132/133





YXL313C-W







YXL172-F



Anti-Explosion Light













YXL324-G

[Power] 200W~720W [Efficiency] 110-150 lm/W [Beam Angle] 30°/ 60°/ 90°

Size] 1-Modular:645X196X260mm 2-Modular:645X415X260mm

3-Modular:645X630X260mm



YGCL542

[Power] 120W~300W [Efficiency] 110-130 lm/W [Beam Angle] 100°

[Size A] 580X70X345mm [Size B] 1150X70X345mm




/ 63 Industrial Light / 64





Hook





YGCL546

70W~200W [Power] [Efficiency] 110-150 lm/W [Beam Angle] 60°/90°/110° [Size A]

Φ280X149mm Shallow shield: Φ380X223mm Deep shield: Φ447X305mm

Ф365X185mm [Size B]

Shallow shield: Φ471X266mm Deep shield: Φ546X361mm

YXL536-G

[Power] 100W~180W [Efficiency] 110-150 lm/W [Beam Angle] 60°/90°/120° [Size A] Ф395X286mm [Size B] Ф460X303mm




YXL538-G

70W~180W [Power] [Efficiency] 110-150 lm/W [Beam Angle] 60°/90°/120° [Size A] Φ410X271mm Φ422X283mm [Size B] [Size C] Ф460X290mm



/65 Industrial Light / 66







YASHIPS



[Power] 100W~200W [Efficiency] 110-130 lm/W [Beam Angle] 90°/120°

[Size A]

Φ277X150mm Shallow shield: Φ380X228mm Deep shield: Φ446X310mm

[Size B]

Φ317X161mm Shallow shield: Φ410X230mm Deep shield: Φ475X317mm

[Size C]

Φ364X158mm Shallow shield: Φ471X243mm Deep shield: Φ546X338mm

YGCL540

[Power] 80W~240W [Efficiency] 130-150 lm/W [Beam Angle] 90°/120° [Size A]

Φ280X167mm Shallow shield: Φ380X245mm Deep shield: Φ447X327mm

[Size B] Ф318X171mm

Shallow shield: Φ416X251mm Deep shield: Φ483X341mm

[Size C]

Φ365X179mm Shallow shield: Φ471X264mm Deep shield: Φ546X359mm

YGCL546

300W~600W [Power] [Efficiency] 110-265V

[Beam Angle] 60°

[Size] Ф600X385mm



LED CANOPY LIGHT



YGWL132

50W~70W [Power] [Efficiency] 110-130 lm/W

[Beam Angle] 120°

[Size] 260X260X87mm

British Control of the Control of th



YGWL133

[Power] 50W~70W [Efficiency] 110-130 lm/W [Beam Angle] 120°

[Size] Ф290X87mm



YXL536-W

100W~180W [Power] [Efficiency] 110-150 lm/W

[Beam Angle] 90°/120° [Size A] 368X360X197mm

[Size B] 428X420X204mm



YXL538-W

[Size C]

[Power] 70W~180W [Efficiency] 110-150 lm/W [Beam Angle] 90°/120° [Size A] Ф300X162mm [Size B] Ф345X173mm Ф380X180mm



[Power] 60W~70W [Efficiency] 110-130 lm/W [Beam Angle] 60°/120° Ф222X192mm [Size]



YXL137-W RESERVED BEING

[Power] 70W~280W [Efficiency] 110-150 lm/W

[Beam Angle] 90°

[Size A] 358X358X148.5mm 458X458X163mm [Size B]



LED GAS STATION LIGHT

LED ANTI-CORROSION LIGHT





YGWL117

[Power] 120W~180W [Efficiency] 110-170 lm/W

[Beam Angle] 90°

[Size A] 400X400X120mm [Size B] 415X415X101.6mm





YXL172-F

[Power] 40W~60W [Efficiency] 110-130 lm/W [Beam Angle] 220°

[Size]

Hanging Type: Φ221X294mm Ceiling Type: Φ221X331mm

/71 Industrial Light /72

LED ANTI-CORROSION LIGHT



YFBL196-D

[Power] 50W~200W [Anti-Explosion Sign] Ex d II C T6 [Size] 310X550X100mm



YFBL196-T

[Power] 50W~500W [Anti-Explosion Sign] Ex d II C T6

[Size]

1-Modular:310X170X120mm 2-Modular:310X310X120mm 3-Modular:460X310X120mm 6-Modular:620X480X180mm 8-Modular:620X600X180mm 10-Modular:720X620X180mm











YFBL197-T

 [Power]
 50W~200W

 [Anti-Explosion Sign]
 Ex d II C T6

 [Size A]
 305X253X168mm

 [Size B]
 450X307X168mm



YFBL197-B

[Power] 30W~60W [Anti-Explosion Sign] Ex d II C T6 [Size] 710X120X100mm 945X120X100mm

YFBL198-C

[Power]	50W~300W
[Anti-Explosion Sign]	Ex d II C T6
[Size A]	Ф245X320mm
[Size B]	Ф300X360mm
[Size C]	Ф420X360mm
[Size D]	Ф470X420mm



/73 Industrial Light /74

LED ANTI-CORROSION LIGHT

LED FIRE EMERGENCY LIGHT



YFBL200-Y

[Power] 16W~32W [Anti-Explosion Sign] Ex d II C T6 [Size] 1280X202X146mm

1280X202X146mm 1280X202X146mm

YFBL201-XZ [Power] < 6W [Anti-Explosion Sign] Ex d II C T6 [Size] 351X196X72mm Ceiling Type




LED FIRE EMERGENCY SIGN LIGHT

YFBL201-XB

A

[Power] < 6W Ex d II C T6 [Anti-Explosion Sign] [Size] 351X196X72mm









/75 Industrial Light / 76

LED ANTI-EXPLOSION HEADLIGHT

LED ANTI-EXPLOSION FLASHLIGHT



YFBL202

[Power] 3W

Ex d II CT4 [Anti-Explosion Sign]

A:7h(Glare)14h(Work light) B:8h(Glare)16h(Work light) [Discharge Time]

73X58X53mm [Size]









YFBL203

[Power] 3W [Anti-Explosion Sign] Ex d II C T6

A/B/C:8h(Hard light)16h(Work light) D:6h(Hard light)12h(Work light) [Discharge Time]

[Size A/B] Ф35X158mm [Size C] Ф28X130mm [Size D] Ф27X145mm



D:Multifunctional Corner Anti-Explosion Flashlight

/77 Industrial Light / 78





Light distribution curve (Applicable items)







LED COMPARTMENT TUNNEL LIGHT

YZDL722

[Power] 5W~18W [Efficiency] 90 lm/W [Beam Angle] 90°/120°

[Size] 350X150X135mm



LED CLASSROOM LIGHT





[Power] 36W~45W [Efficiency] 90 lm/W [Beam Angle] 120°

Size] 1220X200X50mm 1220X300X50mm

LED BLACKBOARD LIGHT

YGPL270

[Power] 36W
[Efficiency] 90 lm/W
[Beam Angle] Polarized Light
[Size] 1195X108X160mm



LED PANEL LIGHT



YGPL200

[Power] 6W~18W [Efficiency] 90 lm/W [Beam Angle] 120°

[Size] 97X97X50mm

160X160X55mm 200X200X55mm



YGPL202

[Power] 20W~48W [Efficiency] 90 lm/W [Beam Angle] 120°

[Size] 295X295X9mm

295X595X9mm 595X595X9mm 1195X295X9mm



YGPL203

[Power] 20W~48W [Efficiency] 90 lm/W [Beam Angle] 120°

[Size] 295X295X35mm 295X595X35mm

295X595X35mm 595X595X35mm 1195X295X35mm



YGPL251

[Power] 12W~72W [Efficiency] 100 lm/W [Beam Angle] 110°

[Size] 295X295X11mm

595X295X11mm 595X595X11mm 1195X295X11mm 1195X595X11mm



YGPL201

[Power] 12W~72W [Efficiency] 100 lm/W [Beam Angle] 110°

[Size] 295X295X11mm

595X295X11mm 595X595X11mm 1195X295X11mm 1195X595X11mm



/ 83 Rail Traffic & Indoor Light / 84

LED BRACKET LIGHT








[Power] 20W~40W [Efficiency] 90 lm/W [Beam Angle] 120°

[Size] 600X65X68mm

1200X65X68mm 1200X65X68mm



LED DOWN LIGHT



LED DOWN LIGHT



YGPL256

[Power] 15W~50W [Efficiency] 100 lm/W [Beam Angle] 38°/50°

[Size] Ф85X85mm

Φ100X105mm Φ125X130mm Ф150X170mm

Ф185X200mm

YGPL253

5W~20W [Power] 90 lm/W [Efficiency] [Beam Angle] 15°/24°/38° Ф100X35mm [Size]









YGPL254

30W [Power] [Efficiency] 90 lm/W [Beam Angle] 25°

[Size] Ф163X135mm

YMXL255

[Power] 30W~50W [Efficiency] 90-110 lm/W [Beam Angle] Ф200X270mm [Size]



LED EMERGENCY SAFETY SIGN LAMP

YGPL260

[Power] 2W 24h [Charging time] [Emergency time] 90min

[Size] 330X140X22mm





/87 Rail Traffic & Indoor Light / 88